

Alignment Condition: Full tank of fuel, no passengers and placed on flat level surface.

Wheel Alignment Specifications

RPO Restriction	Wheels	Caster ± 0.75°		Cross Caster ± 0.75°	Camber ± 0.75°		Cross Camber ± 0.75°	Total Toe ± 0.2°	Steering Wheel Angle ± 3.5°	Thrust Angle ± 0.3°
		Left	Right	(Left - Right)	Left	Right	(Left - Right)	(Left + Right)		(Left - Right)/2
FE2 without WRS	Front	5.9°	5.9°	0.0°	-0.2°	-0.2°	0.0°	0.2°	0.0°	—
	Rear	—	—	—	-0.75°	-0.75°	—	0.2°	—	0.0°
FE2 with WRS	Front	5.9°	5.9°	0.0°	-0.2°	-0.2°	0.0°	0.2°	0.0°	—
	Rear	—	—	—	-0.4°	-0.4°	—	0.2°	—	0.0°
FE3	Front	5.9°	5.9°	0.0°	-0.8°	-0.8°	0.0°	0.2°	0.0°	—
	Rear	—	—	—	-0.4°	-0.4°	—	0.2°	—	0.0°
FE4	Front	5.9°	5.9°	0.0°	-0.8°	-0.8°	0.0°	0.2°	0.0°	—
	Rear	—	—	—	-0.4°	-0.4°	—	0.2°	—	0.0°
FE5	Front	5.6°	5.6°	0.0°	-1.0°	-1.0°	0.0°	0.2°	0.0°	—
	Rear	—	—	—	-0.5°	-0.5°	—	0.2°	—	0.0°
FE6	Front	5.6°	5.6°	0.0°	-1.0°	-1.0°	0.0°	0.2°	0.0°	—
	Rear	—	—	—	-0.75°	-0.75°	—	0.2°	—	0.0°

© 2013 General Motors. All rights reserved.