

[2010 Chevrolet Camaro](#) | [Camaro \(VIN F\) Service Manual](#) | [Engine](#) | [Engine Mechanical - 4.8L, 5.3L, 6.0L, 6.2L, or 7.0L](#)
[Specifications](#) | **Document ID: 2201201**

Fastener Tightening Specifications (6.2L LS3)

Application	Specification	
	Metric	English
Camshaft Position (CMP) Sensor Bolt	12 N·m	106 lb in
CMP Sensor Wire Harness Bolt	12 N·m	106 lb in
Camshaft Retainer Bolts - Hex Head Bolts	25 N·m	18 lb ft
Camshaft Retainer Bolts - TORX® Head Bolts	15 N·m	11 lb ft
Camshaft Sprocket Bolt - First Pass	75 N·m	55 lb ft
Camshaft Sprocket Bolt - Final Pass	50 degrees	
Clutch Pressure Plate Bolts	70 N·m	52 lb ft
Connecting Rod Bolts - First Pass	20 N·m	15 lb ft
Connecting Rod Bolts - Final Pass	85 degrees	
Coolant Air Bleed Pipe Bolts	12 N·m	106 lb in
Coolant Temperature Sensor	20 N·m	15 lb ft
Crankshaft Balancer Bolt - Step 1	150 N·m	111 lb ft
Crankshaft Balancer Bolt - Step 2	Loosen 360 degrees	
Crankshaft Balancer Bolt - Step 3	50 N·m	37 lb ft

Crankshaft Balancer Bolt - (with Flanged Head) Final Step	125 degrees	
Crankshaft Balancer Bolt - (with Retained Rotating Washer) Final Step	200 degrees	
Crankshaft Bearing Cap M10 Bolts - First Pass in Sequence	20 N·m	15 lb ft
Crankshaft Bearing Cap M10 Bolts - Final Pass in Sequence	80 degrees	
Crankshaft Bearing Cap M10 Studs - First Pass in Sequence	20 N·m	15 lb ft
Crankshaft Bearing Cap M10 Studs - Final Pass in Sequence	51 degrees	
Crankshaft Bearing Cap M8 Bolts (1-5) - First Pass	20 N·m	15 lb ft
Crankshaft Bearing Cap M8 Bolts (1-5) - Final Pass	30 N·m	22 lb ft
Crankshaft Bearing Cap M8 Bolts (6-10) - First Pass	20 N·m	15 lb ft
Crankshaft Bearing Cap M8 Bolts (6-10) - Final Pass	30 N·m	22 lb ft
Crankshaft Oil Deflector Nuts	25 N·m	18 lb ft
Crankshaft Position (CKP) Sensor Bolt	25 N·m	18 lb ft
Crankshaft Rear Oil Seal Housing Bolts	30 N·m	22 lb ft
Cylinder Head M11 Bolts - First Pass in Sequence	30 N·m	22 lb ft
Cylinder Head M11 Bolts - Second Pass in Sequence	90 degrees	
Cylinder Head M11 Bolts - Final Pass in Sequence	70 degrees	
Cylinder Head M8 Bolts - in Sequence	30 N·m	22 lb ft
Cylinder Head Coolant Plug	20 N·m	15 lb ft

Engine Block Coolant Drain Hole Plug	60 N·m	44 lb ft
Engine Block Oil Gallery Plug	60 N·m	44 lb ft
Engine Oil Cooler Coolant Hose Bracket-to-Oil Pan	25 N·m	18 lb ft
Engine Oil Cooler Coolant Hose Connector-to-Cooler Housing	35 N·m	26 lb ft
Engine Oil Cooler Core-to-Housing Bolts	25 N·m	18 lb ft
Engine Oil Cooler-to-Oil Pan M6 Bolts	10 N·m	89 lb in
Engine Oil Cooler-to-Oil Pan M8 Bolts	25 N·m	18 lb ft
Evaporative Emission (EVAP) Canister Purge Solenoid Valve Bolt	50 N·m	37 lb ft
Exhaust Manifold Bolts - First Pass	15 N·m	11 lb ft
Exhaust Manifold Bolts - Final Pass	20 N·m	15 lb ft
Exhaust Manifold Heat Shield Bolts	9 N·m	80 lb in
Exhaust Manifold Stud	20 N·m	15 lb ft
Flywheel Bolts - First Pass	20 N·m	15 lb ft
Flywheel Bolts - Second Pass	50 N·m	37 lb ft
Flywheel Bolts - Final Pass	100 N·m	74 lb ft
Front Cover Bolts	25 N·m	18 lb ft
Fuel Injection Fuel Rail Bolts	10 N·m	89 lb in
Ignition Coil Bracket-to-Valve Rocker Arm Cover Stud	12 N·m	106 lb in

Ignition Coil-to-Bracket Bolts	10 N·m	89 lb in
Intake Manifold Bolts - First Pass in Sequence	5 N·m	44 lb in
Intake Manifold Bolts - Final Pass in Sequence	10 N·m	89 lb in
J 41798 M8 Bolt	25 N·m	18 lb ft
J 41798 M10 Bolts	50 N·m	37 lb ft
Knock Sensor Bolts	25 N·m	18 lb ft
Motor Mount Bracket Bolts	50 N·m	37 lb ft
Oil Filter	30 N·m	22 lb ft
Oil Filter Fitting	55 N·m	40 lb ft
Oil Level Indicator Tube Bolt	25 N·m	18 lb ft
Oil Level Sensor	13 N·m	115 lb in
Oil Pan Closeout Cover Bolt - Left Side	9 N·m	80 lb in
Oil Pan Closeout Cover Bolt - Right Side	9 N·m	80 lb in
Oil Pan Drain Plug	25 N·m	18 lb ft
Oil Pan M6 Bolts - Oil Pan-to-Rear Oil Seal Housing	12 N·m	106 lb in
Oil Pan M8 Bolts - Oil Pan-to-Engine Block and Oil Pan-to-Front Cover	25 N·m	18 lb ft
Oil Pressure Relief Valve - In Oil Pan	27 N·m	20 lb ft
Oil Pressure Sensor	35 N·m	26 lb ft

Oil Pump Cover Bolts	12 N·m	106 lb in
Oil Pump Relief Valve Plug	12 N·m	106 lb in
Oil Pump Screen Nuts	25 N·m	18 lb ft
Oil Pump Screen-to-Oil Pump Bolt	12 N·m	106 lb in
Oil Pump-to-Engine Block Bolts	25 N·m	18 lb ft
Spark Plugs	15 N·m	11 lb ft
Throttle Body Bolts	10 N·m	89 lb in
Timing Chain Tensioner Bolts	30 N·m	22 lb ft
Valley Cover Bolts	25 N·m	18 lb ft
Valve Lifter Guide Bolts	12 N·m	106 lb in
Valve Rocker Arm Bolts	30 N·m	22 lb ft
Valve Rocker Arm Cover Bolts	12 N·m	106 lb in
Water Inlet Housing Bolts	15 N·m	11 lb ft
Water Pump Bolts - First Pass	15 N·m	11 lb ft
Water Pump Bolts - Final Pass	30 N·m	22 lb ft